



## Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

---

**Product name : Demulsifier NR-4520**

**Chemical name:** Polymerized Polyol

**Supplier** :NUR Chemicals & Engineering Indus. L.L.C  
 P.O. Box 926948  
 Amman 11190 Jordan  
 Tel.:+962 6 461 9988  
 Fax:+962 6 461 9989  
[www.nurchemicals.com](http://www.nurchemicals.com)

**Emergency Tel. NO.:**+962 6 402 3995

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

---

Component	CAS #	Concentration
Demulsifier blend	NA	59.5 %
Heavy aromatic solvent naphtha	64742-94-5	<36 %
nephtalene	91-20-3	< 4..5 %
oxirane	75-21-9	< 0.001 %

### 3. HAZARDS IDENTIFICATION

---

#### APPEARANCE

**Physical state** Liquid  
**Color** amber  
**Odor** Aromatic

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

## **EMERGENCY OVERVIEW**

**Caution!**

### **COMBUSTIBLE LIQUID**

MAY BE HARMFUL IF SWALLOWED.

NORMAL PRECAUTIONS COMMON TO SAFE MANUFACTURING PRACTICE SHOULD BE FOLLOWED IN HANDLING AND STORAGE.

## **POTENTIAL HEALTH EFFECTS**

### **Swallowing**

#### **Acute effects**

May be harmful if swallowed.

### **Skin absorption**

#### **Acute effects**

Harmful effects are not expected from short periods of contact.

### **Inhalation**

#### **Acute effects**

Short-term harmful health effects are not expected from vapor generated ambient temperature.

### **Skin contact**

#### **Acute effects**

Prolonged contact may cause irritation.

### **Eye contact**

#### **Acute effects**

May cause discomfort

## **POTENTIAL ENVIRONMENTAL EFFECTS**

No information available.

---

## **4. FIRST AID MEASURES**

---

**Swallowing:** Do not induce vomiting. Obtain medical attention immediately.

**Skin:** Wash skin with soap and water.

**Inhalation:** Remove to fresh air. Give artificial respiration if not breathing. Obtain medical attention.

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

**Eye Contact:** Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.

---

## 5. FIRE-FIGHTING MEASURES

---

**Flash point:** 55C°

**Special protective equipment for firefighters**

Use self-contained breathing apparatus when fighting fires in enclosed areas.

**Extinguishing media**

Suitable: Extinguish with:

- Water fog
  - Dry chemical
  - CO2
  - Alcohol resistant foam
- 

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions**

Wear suitable protective equipment.

**Environmental precautions**

Avoid runoff to sewers or waterways. Insoluble in water.

**Methods for cleaning up**

Dike to contain spill. Recover by pumping or scooping into appropriate containers. For small spills use of an absorbent may facilitate collection. Traces of material may be removed by flushing with water to a sewer connected to an appropriate treatment facility.

Absorb on inert material such as sand, earth, vermiculite.

Observe government regulations.

---

## 7. HANDLING AND STORAGE

---

### HANDLING

**Handling precautions**

Do not get in eyes, on skin, on clothing. Keep drums tightly closed to prevent contamination. Wear recommended personal protection equipment. Never use pressure to empty drums.

### STORAGE

**Storage requirements**

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

Keep away from heat, spark and flame and use with adequate ventilation. Store at ambient temperature.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### PERSONAL PROTECTION

#### Respiratory

If personnel exposure exceeds the exposure limits, select appropriate protective equipment in accordance with NIOSH recommendations.

#### Hand protection/protective gloves

Resistant gloves.

#### Eye protection

Safety glasses.

#### Skin protection

Rubber or plastic apron

#### Industrial hygiene measures

Remove contaminated clothing and clean it

## ENGINEERING CONTROLS

### Ventilation

General (mechanical) room ventilation is expected to be satisfactory for normal handling.

### Exposure limits

No exposure limits have been established

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Physical state	Liquid
Color	Amber
Odor	Aromatic

### OTHER PROPERTIES

Boiling point	ND
Melting point	<-18 at STP unless specified below

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

<b>PH</b>	4-6 Connection: 50 g/l
<b>Density</b>	0.97 g/cm <sup>3</sup> at 25 °C
<b>Vapor pressure</b>	ND
<b>Vapor density (air=1)</b>	ND
<b>Solubility in water</b>	Insoluble
<b>Flash point</b>	55 C° Method: Pensky-Martens closed cup ASTM D 93
<b>Percent volatiles</b>	43% (m)

---

## 10. STABILITY AND REACTIVITY

---

**Stability: stable.**

**Stability – Conditions to avoid**

Stable under normal conditions.

**Incompatible materials**

Strong oxidizing agents.

**Hazardous combustion products**

Carbon monoxide.

Carbon dioxide.

**Hazardous polymerization:** will not occur

---

## 11. TOXICOLOGICAL INFORMATION

---

### GENERAL

No information available

---

## 12. ECOLOGICAL INFORMATION

---

No information available

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

---

## 13. DISPOSAL CONSIDERATIONS

---

General: It is our opinion this product is not a RCRA hazardous waste. It is the generator's responsibility to make their own determination as to the RCRA status of waste they generate. We have not performed a Toxicity Characteristic Leachate Procedure (TCLP) on this product. Incinerate in a furnace where permitted under appropriate Federal, State, and local regulations.

### Non-cleaned packages

Dispose of washing solution in the same way as product.

---

## 14. TRANSPORT INFORMATION

---

### DOT Classification

Not regulated by air, road or rail if shipped or transport in containers less than 450 L.

Proper shipping name: COMUSTIBLE LIQUID, N.O.S. (petroleum solvent)

Class: COMUSTIBLE LIQUID

UN ID #: NA 1993

Packing group: III

### IMDG Classification

Proper shipping name: petroleum distillates

Class: 3

UN ID #: UN 1268

Packing group: III

### ICAO Classification

Proper shipping name: petroleum distillates

Class: 3

UN ID #: UN 1268

Packing group: III

---

## 15. REGULATORY INFORMATION

---

**Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40CFR302.4.**

Components present in this product at a level which could require reporting under the statute are: \*\*\*\* NONE \*\*\*\*

**Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQ's) and release**

# Material Safety Data Sheet

**Product name: Demulsifier NR-4520**

---

**reporting based on Reportable Quantities (RQ's) in 40CFR355 (used for SARA 302 and 304).**

Components present in this product at a level which could require reporting under the statute are: None.

**Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40CFR372 (for SARA 313). This information must be included in MSDS's that are copied and distributed for this material.**

Components present in this product at a level which could require reporting under the statute are: None

**Pennsylvania Right -To- Know Hazardous Substance List-Hazardous Substances and Special Hazardous Substances on the list must be identified when present in products.**

Components present in this product at a level which could require reporting under the statute are: None.

---

## 16. OTHER INFORMATION

---

### RECOMMENDED USES AND RESTRICTIONS

Please consult the product and/or application information bulletins for this product.

### HMIS RATING

Health: 1	Flammability: 2	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

### LEGEND

STP	Standard temperature and pressure
W/W	Weight/Weight
0 (HMIS)	Minimal hazard
1 (HMIS)	Slight hazard
2 (HMIS)	Moderate hazard
3 (HMIS)	Serious hazard
4 (HMIS)	Severe hazard
X (HMIS)	Personal protection rating to be supplied by user depending on use conditions